Total Page - 11

UG/2nd Sem/Phys/H/19 (Pr.)

2019

B.Sc. (CBCS)

2nd Semester Examination

PHYSICS (Honours)

Paper - C4P

[Practical]

Full Marks: 20

Time: 3 Hours

The figu res in the margin indicate full marks.

Candidates are required to give their answers in their own words as far as practicable.

Answer one question.

- Determine the frequency of an electric funing fork by Melde's experiment and verify (λ²-T) law for either transverse or longitudinal (with respect to length of the thread) vibration of the tuning fork-arm. [Weight of the hanger and mass per unit length of the thread will be supplied]
 - (a) Working formula.

2

[Turn Over]

Reading for $\lambda^2 - T$	for	five	different
weights on the hanger.			8

- (c) Drawing $\lambda^2 T$ graph.
- (d) Determination of frequency of the tuning fork from the graph.
- 2. Determine the frequency ratio of two Sinusoidal signals from Lissajous figures with the help of a CRO. [Two function generators are to be provided. Frequency of one function generator will be fixed and unknown to the student: frequency of the other function generator will be adjusted so that the ratio of number of loops along two perpendicular axes are 1:1, 2:3, 1:2, 1:3, 1:4 (or any 5 sets of ratio of small integers given by the examiner]
- (a) Theory. 3
- (b) Readings for frequency ratio of two sinusoidal signals.
- (c) Calculation of unknown frequency. 3
- Find the phase difference of two sinusoidal signals from Lissajous Figures with the help of a CRO.

[Signals of different phases can be obtained with the help of an RC circuit driven by a sinusoidal voltage. Voltage across RC combination and voltage across R can be taken as the two signals. Values of R & C are to be given.]

- (a) (i) Working formula for phase difference from Lissajous ellipse.
 - Wroking formula for phase difference of voltages across RC combination and across R.
- (b) Circuit diagram and implementation.
- (c) Readings for phase difference (3 sets for 3 different R)
- (d) Calculation of practical and theoretical phase differences from formula (i) and (ii) and comparison.
- Investigate the normal modes and resonance of coupled pendulum.

[Two identical compound pendula (rod-mass system) of equal time period suspended from a rigid support

[Turn Over]

2

423/4/35-2500

(4)

and coupled by an un-stretched horizontal spiral spring are to be used. Spring constant of the given spring will be supplied.]

(a) Working formula.

4

(b) Readings for time periods of (i) in phase oscillation (T₁), (ii) out of phase oscillation (T₂) (iii) beat oscillations (T_C) and (iv) beats (T_B)

[Reading for at least 30 oscillations in each case is to be taken. Least count of the stop watch is to be noted.]

- (c) Comparison of measured values of T_C and T_B with calculated values.
- (d) Determination of coupling coefficient.
- Determine the dispersive power of the material of a prism using mercury/helium source.
 - (a) Working formula.

2

(b) Performing Schuster's focusing (to be verified by the examiner). (5)

(c) Readings for deviation of three specified colours of mercury/helium source. (Two extreme colours and the mean colour) 6

(d) Readings for direct rays.

2

- (e) Calculation of refractive indices of the three colours and dispersive power.
 2+1
- Determine the Cauchy constants of the material of a prism using mercury/helium source. [Value of minimum scale division and V. C. of spectrometer are to be supplied. Two colours are to be specified and their wavelength will be supplied.]

(a) Working formula.

2

- (b) Performing Schuster's focusing (to be verified by the examiner)
- (c) Readings for deviation of two specified colours of mercury/helium source.
- (d) Readings for direct rays.

(e) Calculation of refractive indices and Cauchy constants.

[Turn Over]

423/4/35-2500

o-	
o-	

(d) Readings for deviation of the specified spectral lines (for any one order)	(9)
(e) Calculation of wavelengths, 2	 Determine the number of rulings per mm of a plane transmission grating. [V. C. of the spectrometer is to be supplied]
Determine resolving power and dispersive power of a plane diffraction grating. [Number of rulings per	(a) Wroking formula. 2
mm (m) and number of rulings illuminated by the collimated incident beam (N) are to be supplied, V. C. of the spectrometer is to be supplied.]	(b) Performing schuster's focusing (to be verified by the examiner) 2
(a) Working formula.	(c) Readings for setting up of the grating surface for normal incidence. 3
(b) Performing Schuster's focusing (to be verified by the examiner) 2	 (d) Readings for deviation of sodium yellow line for three orders. (Wavelength will be supplied by the examiner)
(c) Readings for setting up of the grating surface for normal incidence. 3	(e) Calculation of number of rulings per mm. 2
d) Readings for deviation of two spectral lines specified by the examiner. (Readings for any two orders, as may be specified by the examiner) 6	12. Determine the wavelength of sodium light using Newton's Rings. [Radius of curvature of the convex surface of plano-convex lens and the least count of the micro meter screw are to be supplied]
Calculation of resolving power and dispersive power.	(a) Working formula. 2
	(b) Readings for D ² _w Vs. m (ring number) graph.
	[Take at least 5 readings] 8

[Turn Over]

(10)		* /	n.	'n.
		и	ur.	
	N			•

(4) Calculation of wavelength from the oranh

(c) Drawing D_m² Vs, m graph.

(b) Calculation 2
 Determine the wavelength of sodium source using Michelson's interferometer.
[Least count of the micrometer screw is to be supplied]
(a) Working formula and principle.
(b) Adjustment of the apparatus to obtain sharp circular fringes. (To be verified by the examiner) 2
(c) Readings for the displacement (x) of mirror and number (m) of bright fringes crossing the crosswire. (At least 4 sets of readings for crossing of about 10 fringes in each case) 8
(d) Calculation of wavelength. 2
 Determine the wavelength of sodium light using Fresnel Biprism. [Separation between the virtual sources and least count of the micrometer is to be supplied]

(a) Wroking formula.

423/4/35-2500

(11)

(b) Setting up of the apparatus for obtaining fringes and alignment of the apparatus. (To be verified by the examiner)

(c) Readings for fringe width at two positions of the eyepiece differing by at least 20 cm. (At each position at least 4 readings with a gap of three fringes in between two readings are to be taken)

(d) Calculation of wavelength.

2

LNB - 2, Viva-Voce - 3, Expt. - 15.